



Electronic Grade China Factory Price High Purity 6n Cylinder Gas Sih4 Gas Silane

Our Product Introduction

for more products please visit us on gascylindertank.com

Basic Information

- Place of Origin: China
- Brand Name: CMC
- Certification: COA
- Model Number: sih4
- Minimum Order Quantity: 1kg
- Price: US \$45/kg
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 50000kg/month



Product Specification

- Product Name: Silane
- Melting Point: -185 °C
- Appearance: Colorless, Garlic Smell
- Boiling Point: -112 °C
- Cylinder Pressure: 12.5MPa/15MPa/20MPa
- Valve: Diss632
- Cylinder Standard: GB/ISO/DOT
- Transport Package: Y-Cylinder, T-Drum, T-Cylinder, T-Drum, Tt, Tanker
- Specification: 20L, 40L, 280L And Customizable
- Trademark: CMC
- Origin: Suzhou, China
- HS Code: 2812190091
- Supply Ability: 50000kg/Month
- CAS No.: 7803-62-5



More Images



Product Description

Product Description

Silane refers to a group of chemical compounds that contain a silicon atom bonded to hydrogen atoms. The most common and simplest form of silane is monosilane (SiH₄). Here are some key points about silane:

Structure: Silane has a tetrahedral structure, with a central silicon atom bonded to four hydrogen atoms. The chemical formula for monosilane is SiH₄.

Properties: Silane is a colorless, flammable gas with a pungent odor. It is less dense than air and can form explosive mixtures when exposed to air. Silane is highly reactive and can react with oxygen, water, and other compounds.

Production: Silane can be produced through various methods, such as the reaction of silicon with hydrogen or the hydrolysis of silicon halides. Industrial-scale production often involves the reaction of metallurgical-grade silicon with hydrogen chloride.

Applications: Silane has several applications in different industries:

Semiconductor Industry: Silane is used as a precursor gas in the production of silicon-based materials, such as silicon wafers and thin-film silicon solar cells. It is an important source of silicon for the deposition of amorphous and polycrystalline silicon films.

Chemical Industry: Silane derivatives are used as coupling agents, adhesion promoters, and surface modifiers in various formulations such as coatings, adhesives, and sealants. They can enhance the bonding between different materials, such as glass, metal, and plastics.

Electronics Industry: Silane is involved in the manufacturing of electronic components, including integrated circuits and flat-panel displays. It is used for the deposition of silicon-based thin films for insulation, passivation, and other purposes.

Solar Energy: Silane is used in the production of silicon-based photovoltaic cells, which convert sunlight into electricity.

It is important to note that silane is a highly reactive and potentially hazardous compound, requiring careful handling and storage due to its flammability and reactivity. Safety precautions should be followed when working with silane to mitigate the risks associated with its use.

Basic Info.

Model NO.	SiH ₄	Boiling Point	-112 °C
Density	1.34 Kg/M ³	Melting Point	-185 °C
Cylinder Pressure	12.5MPa/15MPa/20MPa	Transport Package	47L/440L/ISO Tank
Specification	47L/440L/ISO Tank	Origin	China
HS Code	2931900090	Production Capacity	20, 000tons/Year

Specification:

CAS No.: 7803-62-5

EINECS No.: 232-263-4

UN No.: UN2203

Purity: 99.9999%

Dot Class: 2.1

Appearance: Colorless

Grade Standard: Electronic Grade

Specification	99.9999%
Carbon Monoxide	≤ 0.05 ppm
Carbon Dioxide	≤ 0.05 ppm
Total chloride	≤ 0.1 ppm
Methane	≤ 0.05 ppm
C2-C4	≤ 0.1 ppm
Nitrogen	≤ 0.5 ppm
Oxygen	≤ 0.05 ppm
Moisture	≤ 0.1 ppm
Silyl Ether	≤ 0.1 ppm
Methyl Silane	≤ 0.1 ppm
Disilane	≤ 0.3 ppm
Hydrogen	≤ 20 ppm
Aluminum	≤ 0.02 ppba
Antimony	≤ 0.02 ppba
Arsenic	≤ 0.02 ppba
Gallium	≤ 0.02 ppba
Boron	≤ 0.02 ppba
Phosphorus	≤ 0.02 ppba
Iron + Chromium + Nickel + Copper + Zinc	≤ 1 ppba

Detailed Photo



Packaging & Shipping

Cylinder Specifications Contents

Cylinder Capacity	Valve	Weight
47L	DISS632	10 kgs
440L	DISS632	120 kg

Company

Profile



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc ., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine , etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe.

Our products mainly include: H₂, O₂, N₂, Ar, CO₂, propane, acetylene, helium, laser mixed gas, SiH₄, SiH₂Cl₂, SiHCl₃, SiCl₄, NH₃, CF₄, NF₃, SF₆, HCL, N₂O, doping mixed gas (TMB, PH₃, B₂H₆) and other electronic gases.

SiCl ₄	NH ₃	NH ₃	CH ₃ F	SiH ₄	Kr	H ₂ S	WF ₆	F ₆ +Cl ₂
4MS	C ₃ F ₈	C ₃ F ₈	TEOS	CH ₄	PH ₃	SF ₆	C ₂	HCl+Ne
CF ₄	C ₄ F ₈	SiH ₂						TMB+H ₂
SiF ₄	C ₃ H ₈	Cl ₂						He +As
BBr ₃	C ₃ H ₆	DCE						Ge+Se
POCl ₃	N ₂	SO ₂						D+B
BCl ₃	D ₂	CO ₂						CO+NO
SiHCl ₃	CH ₂ F ₂	HF						Ar+O ₂
TMAI	DMZn	DEZn						Xe+NO
AsH ₃	C ₂ H ₄	C ₂ H ₂						
GeH ₄	C ₂ H ₆	B ₂ H ₆						
H ₂ Se	GeCl ₄							



